a first ingredient solute comprising a silicone oil and a first solvent;

a second ingrédient solute comprising a polymethacrylic acid alkyl ester and a second solvent;

a clearing agent comprising amides and being added to a mixture of the first and second ingredient solutes in an amount effective to dissolve the silicone oil and the polymethacrylic acia alkyl ester to form a clear solution; and

a functional agent selected from the group consisting of a resin and a fatty acid alkyl ester, the functional agent being added to the mixture of the first and second ingredient solutes in an amount effective to impart a desired coating feature to the clear solution.

- 2. A coating solution according to claim 1; wherein the clearing agent comprises a compound of the amides selected from the group cohsisting of formamide, acetamide, and formohydrazide.
- 3. A coating solution according to claim 1; wherein the functional agent comprises the resin made of a rosin, which 25 is added to impart a glossing feature to the clear solution.

5

The first that the second of the first of the second of th 15

20

4. A coating solution according to claim 1; wherein the functional agent comprises the fatty acid alkyl ester composed of a palmitic acid alkyl ester, which is added to impart a smoothing feature to the clear solution.

5

5. A coating solution according to claim 1; wherein the first and second solvents comprise at least one compound selected from the group consisting of terpenic oil, heptane, 2-butanone and 1,4 dioxane.

6. A method of producing a coating solution for coating a material, comprising the steps of:

producing a first ingredient solute comprising a silicone oil and a first solvent;

producing a second ingredient solute comprising a polymethacrylic acid alkyl ester and a second solvent;

adding a clearing agent comprising amides to a mixture of the first and second ingredient solutes in an amount effective to dissolve the silicone oil and the polymethacrylic acid alkyl ester to form a clear solution; and

20

U

adding a functional agent selected from the group consisting of a resin and a fatty acid alkyl ester, to the mixture of the first and second ingredient solutes in an amount effective to impart a desired coating feature to the clear solution.

25

5

8. A method according to claim 6; wherein the functional agent comprises the resin made of a rosin, which is added to impart a glossing feature to the clear solution.

10

9. A method according to claim 6; wherein the functional agent comprises the fatty acid alkyl ester composed of a palmitic acid alkyl ester, which is added to impart a smoothing feature to the clear solution.

15

10. A method according to claim 6; wherein the first and second solvents comprise at least one compound selected from the group consisting of terpenic oil, heptane, 2-butanone and 1,4 dioxane.

add a47